



WPFO0205--A
INSULATING BASECOAT WHITE WATERBORNE FILLER

Descriptive notes White waterborne thixotropic basecoat for outdoor. Specific for outdoor joinery, it is a stain protector and also tannin stain inhibitor.

USAGE

Suitable for	Outdoor joinery	Fences	Windows/Balconies			
Method of application	Airless	Air mixing	Spray			

MAIN PROPERTIES

Filling	Good	Sanding	Good
Drying	Medium/slow	Resistance of overcoating	High

PREPARATION OF THE PRODUCT

	Code	%	Descriptive notes
Recommended thinner	Water	0÷5	Only if necessary for application with a cup gun
Other thinners			
Recommended hardener			
Other hardeners			
Accelerant.			

CHEMICAL-PHYSICAL CHARACTERISTICS		APPLICATION CHARACTERISTICS		DRYING	
Specific gravity (kg/l) ±0.03	1,24	N° of coats	1		
Solids Content (%) ±1	50	Qty. per coat (g/m²)	200÷250		
				Sandable (h)	24
Brookfield	15000÷17000 cP			Stackable (h)	12

Additional information:

- Sanding the substrate using 120÷150 sandpaper and clean the surface after sanding.
- Store the product in room where the temperature does not fall below 5°C. ■ During application, keep the product and the substrate at a temperature of at least 15°C.
- Wash immediately after use the tools with water and detergent.

APPLICATION INSTRUCTIONS • Air gun: nozzle 1.9÷2.5, air pressure 2÷3 bar; Airmix: nozzle 9÷11, air pressure 0.5÷1 bar, Airless: nozzle 9÷11.

■ If properly stored, the shelf-life is 6 months.

Overcoatings with Topcoat type	Water based products for outdoor			
---------------------------------------	----------------------------------	--	--	--

WARNING Our data sheets are drawn up on the basis of average results of our trials. However our tech tips are given in good faith but without guarantee. In fact, several media, conditions of application, plant and dilutions are an integral part of the final result and often beyond our control. The user must try the products supplied to test whether suitable to your needs. For our part we guarantee the continuity of the chemical-physical characteristics.

Warning: it is the user's responsibility to provide that the application is in properly ventilated environment hygienic and in accordance with standards and accident prevention regulations currently in force.

Revision n° 3	Revision Date 16/05/23	Printed: 16/05/2023
---------------	------------------------	---------------------