



WTVE800000
SOFT MATT WATER BASED TOP COAT

Descriptive notes Water-based varnish formulated with special resins and additives to obtain excellent surface hardness and softness to the touch.

Gloss Versions	3 - 5							
-----------------------	-------	--	--	--	--	--	--	--

USAGE

Suitable for	Cabinet doors	Furniture	Artisans				
Method of application	Spray	Automatic spraying	Air mixing spray painting				

MAIN PROPERTIES

Transparency	High	Yellowing Resistance	High
		Scratch Resistance	High

PREPARATION OF THE PRODUCT

	Code	%	Descriptive notes
Recommended thinner	Water	10 - 15	Add after mixing of the hardener
Other thinners			
Recommended hardener	INUR0600	15	Mix with a low / medium speed mechanical stirrer
Other hardeners			
Accelerant.			

CHEMICAL-PHYSICAL CHARACTERISTICS		APPLICATION CHARACTERISTICS		DRYING	
Specific gravity (kg/l) ±0.03	1,06	N° of coats	1	Dust free (min)	40
Solids Content (%) ±1	41	Qty. per coat (g/m²)	120 - 130	Touch dry (min)	120
Viscosity DIN 4 (20°C)	55" - 65"				
Pot-Life at 20°C (h)	> 2				

Additional information: The product is formulated only in opacity shown above. To obtain a perfect uniformity of opacity, oven-dry at 40 ° C after the dust-free time.

WARNING Our data sheets are drawn up on the basis of average results of our trials. However our tech tips are given in good faith but without guarantee. In fact, several media, conditions of application, plant and dilutions are an integral part of the final result and often beyond our control. The user must try the products supplied to test whether suitable to your needs. For our part we guarantee the continuity of the chemical-physical characteristics.
Warning: it is the user's responsibility to provide that the application is in properly ventilated environment hygienic and in accordance with standards and accident prevention regulations currently in force.

Revision n° 3	Revision Date 19/05/2020	Printed: 19/05/2020
---------------	--------------------------	---------------------